

# **AUTOMIX CT AND CTR**







Pl-control with microprocessor

0.8 kg

#### **TECHNICAL DATA**

Type of control Voltage Adapter Power consumption Angle of rotation Torque Running time Temperature range AM CT Temperature range AM CTR Ambient temperature Max. temperature of sensor Manual operation Operation signals Protection type Dimensions Weight AM CT Weight AM CTR

230/18 VAC 50/60 Hz 230/18 VAC 200 mA with 1.7 m wire 3 VA 90°, electrically limited 5 Nm 140 sec 0°C - 90°C, stepless 10°C - 80°C, stepless -10°C - 80°C Tmax +110°C Yes, when necessary Two LEDs for indication IP 40 80 x 90 x 93 mm 0.6 kg AUTOMIX CT and CTR are compact electronic constant temperature controls designed to operate 3- and 4-way mixing valves in radiant floor heatings, solid fuel and industrial applications. The supply water temperature can be selected steplessly from 0°C to 90°C with CT and from 10°C to 80°C with CTR.

AUTOMIX CT and CTR are easy to mount on new as well as existing valves. The main supply and the sensors have plug-in connections which minimizes installation problems in the field. The simple and quick do-it-your-self installation saves on labor charges.

# **AUTOMIX CT INCLUDES**

- 1. AUTOMIX CT valve motor 24 VAC 50/60 Hz with built-in electronics
- 2. Mounting kit
- 3. Supply temperature sensor T1 with 1 m wire
- 4. Adapter 230/18 VAC 200 mA with 1.7 m wire

## **AUTOMIX CTR INCLUDES**

- 1. AUTOMIX CT valve motor 24 VAC 50/60 Hz with built-in electronics
- 2. Remote control with 15 m wire
- 3. Mounting kit
- 4. Supply temperature sensor T1 with 1 m wire
- 5. Adapter 230/18 VAC 200 mA with 1.7 m wire

## **ORDERING DATA**

- Order No. Type
- 1320 AUTOMIX CT constant temperature control
- 1321 AUTOMIX CTR constant temperature control with remote control



LK ACASO AB Box 634 SE-521 21 Falköping Tel: +46 515 107 50 Fax: +46 515 590 30

E-mail: info@lkacaso.se Internet: www.lkacaso.se





